

Protectorshell-SP (Single Part)

Traditional clip-together Protectorshell convenience in a single-part design to minimize inventory and simplify underwater laying in poor visibility, etc. The clean, robust design you have come to expect from Protectorshell with added convenience and simplicity.



PS170-SP/500/10

Specifications

Segment Length - Overall	572mm
Effective Installed Length/segment pair	500mm
Minimum Internal Diameter	170mm – recommended for cables up to 153mm Dia
Maximum External Diameter	311/322mm
Wall Thickness	10mm
Material	Ductile Iron to AS1831/ISO 1083/JS/400-15/S
Tensile Strength / Elongation	400MPa / 15%
Impact Resistance	12m Drop test or 26kg
Minimum Bend RADIUS	3.8m Nom. / 3.3m Min.
Weight per Segment	30.06kg
Weight per installed metre (air)	60.12kg
Weight per installed metre (water)	51.48kg

Protectorshell SL

C Regata Cutty Sark No 21 4 IZ 15002 La Coruña, Spain
T: +34 8 8124 1115 F: +34 8 8192 4978

www.protectorshell.com

MS Diversified Services Pty Limited

PO Box 150 Maroubra NSW 2035 Australia
1135 Anzac Parade, Matraville, NSW 2036 Australia
T: +61 2 9694 1004 F: +61 2 9314 3526